



XLynk™

48A Level 2 Charger
Modular EVSE

EZ SWAP FACEPLATE™



KEY FEATURES

- » EZ Swap Faceplate™
- » Buy America options available
- » Local load management
- » Customizable backlit logo

LIFETIME WARRANTY

Lynkwell offers a lifetime warranty on the XLynk™, making it the first and only for a commercial EV charging station.

Electrical

- Configurable current limit settings ranging from 12A to 48A
- Rated voltage: 208-240V AC at 60Hz
- Charging power: 11.5kW at 240V
- Ground fault detection 20mA CCID, auto reset
- Power measurement accuracy +/- 1.0%
- Open ground detection

Connector and Cable

- Single SAE J1772
- High-quality flexible cable
- 18ft / 25ft cable options

Networking and Communications

- Gateway (Wi-Fi and LTE) & non-gateway (Wi-Fi only) units available
- Cellular LTE CAT.M1
- Wi-Fi 2.4GHz 802.11 b/g/n
- Connect up to 9 XLynk™ non-gateway units to 1 XLynk™ gateway unit
- Over-the-air firmware updates
- Network Protocol OCPP 1.6J

Environment

- NEMA 3R rated for indoor and outdoor use
- Meets UL 50E standard for enclosures
- Operating temperature: -22°F to 122°F (-30°C to 50°C)
- Storage temperature: -22°F to 140°F (-30°C to 60°C)
- Humidity: 95% RH non-condensing
- Altitude: 15,000ft (per MIL-STD-810H, 500.6)
- Shock (per MIL-STD-810H, 516.8)
- Vibration (per MIL-STD-810H 514.8)

Standards and Compliance

- Energy Star • UL 2231-1, UL 2231-2,
- OCPP 1.6J UL 2594, UL 991, UL 1998
- FCC Part 15

User Interface

- Display screen provides information about:
 - » Connectivity, charging status, price per kWh, idle fee, charging time, max current output, energy dispensed, running cost, firmware version, and fault status
- Display dimensions: 2.7in (W) x 1.5in (H)
- Display resolution: 128 px x 64 px
- LED Status indicators
- Customizable logo and LED color

Status Indicators

- The LED status lights are highly visible indicators:
 - » Green - available / preparing
 - » Blue - charging
 - » Yellow - booting / configuration / firmware upgrade
 - » Red - faulted / unavailable

Device Specs

- Wall or pedestal mounted
- Power line knockout options available
- Bracket dimensions:
3.4in (W) X 8.8in (H) X 0.7in (D)
- Device dimensions:
6.1in (W) X 14.1in (H) X 4.5in (D)
- Weight: 17lb (18ft cable), 21lb (25ft cable)

Warranty

- Lifetime warranty with pay-as-you-go option

Made in the USA with global parts

Lynkwell's co-located hardware manufacturing, operations, software, support, and service team are proudly based in the U.S. Buy America Compliant XLynk™ options are readily available.

Scan QR Code



Contact Form



lynkwell.com

Follow us  