



## LW201-AC32

32A Level 2 Charger

### KEY FEATURES

- » UL, ES, CTEP certified
- » Pedestal or wall mounted

### Recommended Applications

- » Low-cost multi-unit apartment charger

## Electrical

- Input Current: 32A max
- Input Voltage: 208-240V AC at 50/60Hz
- Max Charging Power: 7.68kW
- Hardwired connection

## Connector and Cable

- Single J1772
- High-quality flexible cable
- Cable length 18' and 25'

## Networking and Communications

- Gateway (Wi-Fi & LTE) & Non-Gateway (Wi-Fi only) units available
- Connect up to 9 non-gateway units to 1 gateway unit
- Ethernet port
- Over-the-air firmware updates are automatic when connected to the Lynkwell network
- Local load management capable

## Environment

- Indoor and outdoor rated NEMA 4
- Operating Temperature:  
-22°F to 122°F (-30°C to 50°C)
- Storage Temperature:  
-22°F to 158°F (-30°C to 70°C)
- Humidity: 95% RH non-condensing

## Display and Indicators

- OLED Dot matrix display
- LEDs provide highly visible EVSE status indicators

## Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):  
7.5" X 11" X 3.2"
- Weight: 14lb (6.35kg)

## Standards and Compliance

- UL Certified
- Energy Star
- SAE J1772
- FCC Part 15B
- CTEP
- OCPP 1.6J

## Other Features and Options

- RFID optional

