



LW202-AC48

48A Level 2 Charger

KEY FEATURES

- » UL, EnergyStar & CTEP certified
- » OCPP 2.0.1
- » High reliability

Recommended Applications

- » Robust public/private/fleet Level 2 charger

Electrical

- Input Current: 48A max
- Input Voltage: 208-240V AC at 60Hz
- Max Charging Power: 11.5kW
- Hardwired connection

Connector and Cable

- Single J1772
- High-quality flexible cable
- Cable length 18' and 25'

Networking and Communications

- Gateway (Wi-Fi & LTE) & Non-Gateway (Wi-Fi only) units available
- Connect up to 9 non-gateway units to 1 gateway unit
- Ethernet port
- ISO 15118
- Over-the-air firmware updates are automatic when connected to the Lynkwell network
- Local load management capable

Environment

- Indoor and outdoor rated NEMA 4
- Operating Temperature:
-22°F to 122°F (-30°C to 50°C)
- Storage Temperature:
-22°F to 176°F (-30°C to 80°C)
- Humidity: 95% RH non-condensing
- Impact Resistance: IK10

Display and Indicators

- 3.5" LCD screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):
8.2" X 11.8" X 3.8"
- Weight: 15.4lb (7kg)

Standards and Compliance

- UL Certified
- Energy Star
- SAE J1772
- FCC Part 15B
- CTEP
- OCPP 1.6J / 2.0.1

Other Features and Options

- RFID enabled
- Credit card reader available

