



KEY FEATURES

- » EnergyStar & CTEP certified
- » ISO 15118
- » Pedestal or wall-mounted

Electrical

- Input Voltage: 408-528V AC at 50/60Hz
- Input Current: 45A
- Output Voltage: 200-1000V DC
- Output Current: 100A
- Output Power: 30kW
- Power Factor: >0.98
- Efficiency: >94% at full load

Connector and Cable

- Single CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 16.4'

Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:
-31°F to 131°F (-35°C to 55°C)
- Storage Temperature:
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,560' above sea level
- Impact Resistance: IK10

Display and Indicators

- 7" touch screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):
26.8" X 17.3" X 11.2"
- Weight: 66.14lb (30kg)

Standards and Compliance

- UL Certified
- CSA
- FCC Part 15A
- CTEP
- OCPP 1.6J
- Energy Star

Other Features and Options

- RFID enabled
- Credit card reader available

