



LW301-DC60

DC Fast Charger Dual Port
60kW max

KEY FEATURES

- » EnergyStar certified
- » ISO 15118
- » Wall and pedestal mount options
- » Integrated cable management

Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 90A
- Output Voltage: 200-1000V DC
- Output Current: 200A
- Output Power: 60kW
- Power Factor: >0.99
- Efficiency: >95% at full load
- 30 kW per plug while simultaneously charging

Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 14.76'

Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:
-22°F to 131°F (-30°C to 55°C)
- Storage Temperature:
-22°F to 158°F (-30°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,560' above sea level
- Impact Resistance: IK10

Display and Indicators

- 7" touch screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):
29.5" X 29.5" X 15"
- Weight: ~275lb (125kg)

Standards and Compliance

- UL Certified
- FCC Part 15A
- Energy Star
- OCPP 1.6J
- CTEP
- TUV

Other Features and Options

- RFID enabled
- Credit card reader available

