



## LW401-DC200

DC Fast Charger Dual Port  
200kW max

### KEY FEATURES

---

- » 32-inch touchscreen
- » Simultaneous charging
- » ISO 15118
- » Buy America compliant options available

# LW401-DC200

## Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 270A
- Output Voltage: 150-1000V DC
- Output Current: 350A (500A Boost)
- Output Power: 200kW
- Power Factor: >0.95
- Efficiency: >95% at full load
- 100kW per plug while simultaneously charging

## Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 19.7'
- Cable management included

## Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118-2
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

## Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:  
-31°F to 131°F (-35°C to 55°C)
- Storage Temperature:  
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,561'
- Impact Resistance: IK10

## Display and Indicators

- 32" FHD touch screen
- Resolution: 1920p X 1080p
- LEDs provide highly visible EVSE status indicators
- Customizable LED color

## Device Mounting

- Ground
- Device dimensions (WxHxD):  
27.5" X 80.7" (90.9" w/ LED Banner) X 27.5"
- Weight: 1102lb (500kg)  
With LED Banner: 1146lb (520kg)

## Standards and Compliance

- UL Certified
- Energy Star
- CSA
- FCC Part 15
- CTEP (NTEP)
- DIN70121
- NRTL (UL)
- OCPP 1.6J / 2.0.1

## Other Features and Options

- LED Banner (option)
- RFID enabled
- Buy America compliant options available
- Credit card reader available

