


XLynk™ LW101-AC48



XLynk

48A Level 2 Charger
Modular EVSE

EZ-SWAP FACEPLATE™



KEY FEATURES

- EZ-Swap Faceplate™
- Buy American Build America (BABA)
Act compliant options available
- Local load management
- Customizable backlit logo

Lifetime Warranty

Lynkwell offers a lifetime warranty on the XLynk, making it the first and only for a commercial EV charging station.

Electrical

- Configurable current limit settings ranging from 12A to 48A
- Rated voltage: 208-240V AC at 60Hz
- Charging power: 11.5kW at 240V
- Ground fault detection 20mA CCID, auto reset
- Power measurement accuracy +/- 1.0%
- Open ground detection

Connector and Cable

- Single SAE J1772
- High-quality flexible cable
- 18ft / 25ft cable options

Networking and Communications

- Gateway (Wi-Fi and LTE) & non-gateway (Wi-Fi only) units available
- Cellular LTE CAT.M1
- Wi-Fi 2.4GHz 802.11 b/g/n
- Connect up to nine XLynk™ non-gateway units to one XLynk™ gateway unit
- Over-the-air firmware updates
- Network Protocol OCPP 1.6J

Environment

- NEMA 3R rated for indoor and outdoor use
- Meets UL 50E standard for enclosures
- Operating temperature: -22°F to 122°F (-30°C to 50°C)
- Storage temperature: -22°F to 140°F (-30°C to 60°C)
- Humidity: 95% RH non-condensing
- Altitude: 15,000ft (per MIL-STD-810H, 500.6)
- Shock (per MIL-STD-810H, 516.8)
- Vibration (per MIL-STD-810H 514.8)

Standards and Compliance

- Energy Star
- OCPP 1.6J
- FCC Part 15
- UL 2231-1, UL 2231-2, UL 2594, UL 991, UL 1998

User Interface

- Display screen provides information about:
 - Connectivity, charging status, price per kWh, idle fee, charging time, max current output, energy dispensed, running cost, firmware version, and fault status
- Display dimensions: 2.7in (W) x 1.5in (H)
- Display resolution: 128 px x 64 px
- Customizable logo and LED color
- LED status indicators

Status Indicators

- The LED status lights are highly visible indicators:
 - Green - available / preparing
 - Blue - charging
 - Yellow - booting / configuration / upgrading
 - Red - faulted / unavailable

Device Specs

- Wall or pedestal mounted
- Power line knockout options available
- Bracket dimensions:
3.4in (W) X 8.8in (H) X 0.7in (D)
- Device dimensions:
6.1in (W) X 14.1in (H) X 4.5in (D)
- Weight: 17lb (18ft cable), 21lb (25ft cable)

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

**Made in the USA
with global parts**



Lynkwell's co-located hardware manufacturing, operations, software, support, and service team are proudly based in the U.S. Buy American Build America (BABA) Act compliant options available.

lynkwell.com

Follow us



(833) 611-LYNK

Scan QR Code



Contact Form