



LW201-AC32

32A Level 2 Charger

KEY FEATURES

- » EnergyStar and CTEP certified

Recommended Applications

- » Level 2 charger, ideal for multi-unit apartment complexes or longer term parking

Electrical

- Input Current: 32A max
- Input Voltage: 208-240V AC at 50/60Hz
- Max Charging Power: 7.6kW
- Hardwired connection

Connector and Cable

- Single J1772
- High-quality flexible cable
- Cable length 18ft and 25ft

Networking and Communications

- Gateway (Wi-Fi & LTE) & Non-Gateway (Wi-Fi only) units available
- Connect up to 9 non-gateway units to 1 gateway unit
- Over-the-air firmware updates are automatic when connected to the Lynkwell network
- Local load management capable

Environment

- Indoor and outdoor rated NEMA 4
- Operating Temperature:
-31°F to 131°F (-35°C to 55°C)
- Storage Temperature:
-40°F to 176°F (-40°C to 80°C)
- Humidity: 95% RH non-condensing
- Altitude: Operational up to 6,560ft above sea level
- Impact Resistance: IK10

Display and Indicators

- Display dimensions (WxH): 3in X 1in
- OLED Dot matrix display
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):
7.5in X 11in X 3in
- Weight: 7lb (3.2kg)

Standards and Compliance

- UL Certified
- Energy Star
- SAE J1772
- FCC Part 15B
- CTEP
- OCPP 1.6J

Other Features and Options

- RFID optional

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

