



LW202-AC48

48A Level 2 Charger

KEY FEATURES

- » UL, EnergyStar & CTEP certified
- » OCPP 2.0.1
- » High reliability

Recommended Applications

- » Robust public/private/fleet Level 2 charger

Electrical

- Input Current: 48A max
- Input Voltage: 208-240V AC at 60Hz
- Max Charging Power: 11.5kW
- Hardwired connection

Connector and Cable

- Single J1772
- High-quality flexible cable
- Cable length 18ft and 25ft

Networking and Communications

- Gateway (Wi-Fi & LTE) & Non-Gateway (Wi-Fi only) units available
- Connect up to 9 non-gateway units to 1 gateway unit
- Ethernet port
- ISO 15118
- Over-the-air firmware updates are automatic when connected to the Lynkwell network
- Local load management capable

Environment

- Indoor and outdoor rated NEMA 4
- Operating Temperature:
-22°F to 122°F (-30°C to 50°C)
- Storage Temperature:
-22°F to 176°F (-30°C to 80°C)
- Humidity: 95% RH non-condensing
- Impact Resistance: IK10

Display and Indicators

- 3.5in LCD screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):
8.2in X 11.8in X 3.8in
- Weight: 15.4lb (7kg)

Standards and Compliance

- UL Certified
- Energy Star
- SAE J1772
- FCC Part 15B
- CTEP
- OCPP 1.6J / 2.0.1

Other Features and Options

- RFID enabled
- Credit card reader available

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

