

LW301-DC180



LW301-DC180

DC Fast Charger Dual Port
180kW max

KEY FEATURES

- » Upgradable power: 120, 150 or 180kW
- » Simultaneous charging
- » ISO 15118
- » CTEP Certified
- » Buy America compliant options available

Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 250A
- Output Voltage: 200-1000V DC
- Output Current: 300A
- Output Power: 180kW
- Power Factor: >0.98
- Efficiency: >94% at full load
- Hardwired connection
- Dynamic power sharing in 30kW increments

Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 16.4ft
- Trapezoidal swing arm for cable management

Networking and Communications

- Wi-Fi, Ethernet, 4G
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:
-22°F to 131°F (-30°C to 55°C)
- Storage Temperature:
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,561ft
- Impact Resistance: IK10

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

Display and Indicators

- 10.4in touch screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Ground
- Device dimensions (WxHxD):
31.5in X 29.5in X 80.7in
- Weight: ~992lb (450kg)

Standards and Compliance

- UL Certified
- FCC Part 15A
- OCPP 1.6J
- Energy Star

Other Features and Options

- RFID enabled
- Credit card reader available
- Buy America compliant options available

