



KEY FEATURES

- » EnergyStar & CTEP certified
- » ISO 15118
- » Pedestal or wall-mounted

Electrical

- Input Voltage: 408-528V AC at 50/60Hz
- Input Current: 45A
- Output Voltage: 200-1000V DC
- Output Current: 100A
- Output Power: 30kW
- Power Factor: >0.98
- Efficiency: >94% at full load

Connector and Cable

- Single CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 16.4ft

Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:
-31°F to 131°F (-35°C to 55°C)
- Storage Temperature:
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,560ft above sea level
- Impact Resistance: IK10

Display and Indicators

- 7in touch screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):
26.8in X 17.3in X 11.2in
- Weight: 66.14lb (30kg)

Standards and Compliance

- UL Certified
- CSA
- FCC Part 15A
- CTEP
- OCPP 1.6J
- Energy Star

Other Features and Options

- RFID enabled
- Credit card reader available

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

