

LW301-DC320



LW301-DC320

DC Fast Charger Dual Port
320kW max

KEY FEATURES

- » Nearly double the power of the 180kW unit, with no increase in footprint
- » All in one cabinet
- » CTEP Certified
- » ISO 15118
- » Buy America compliant options available

Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 415A
- Output Voltage: 150-1000V DC
- Output Current: 300A (15 min at 500A max)
- Output Power: 320kW
- Power Factor: ≥ 0.98
- Efficiency: $>97\%$ at full load
- Dynamic power sharing in 80kW increments

Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 16.4ft or 19.7ft
- Swing arm for cable management (included)

Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R / IP55
- Operating Temperature:
-22°F to 131°F (-30°C to 55°C)
- Storage Temperature:
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,561ft above sea level
- Impact Resistance: IK10

Display and Indicators

- 10in touch screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Ground
- Device dimensions (WxHxD):
2.6ft X 7.2ft X 2.4ft
- Weight (excluding power modules): ~1080lb (490kg)

Standards and Compliance

- UL Certified
- Energy Star
- FCC Part 15A
- OCPP 1.6J
- CTEP
- OCPP 2.0 in development
- OCA

Other Features and Options

- RFID enabled
- Buy America Compliant options are available
- Credit card reader available

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

