



## LW301-DC60

DC Fast Charger Dual Port  
60kW max

### KEY FEATURES

- » EnergyStar certified
- » ISO 15118
- » Wall and pedestal mount options
- » Integrated cable management

## Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 90A
- Output Voltage: 200-1000V DC
- Output Current: 200A
- Output Power: 60kW
- Power Factor: >0.99
- Efficiency: >95% at full load
- 30 kW per plug while simultaneously charging

## Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 14.76ft

## Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

## Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:  
-22°F to 131°F (-30°C to 55°C)
- Storage Temperature:  
-22°F to 158°F (-30°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,560ft above sea level
- Impact Resistance: IK10

## Display and Indicators

- 7in touch screen
- LEDs provide highly visible EVSE status indicators

## Device Mounting

- Pedestal or wall-mount
- Device dimensions (WxHxD):  
29.5in X 29.5in X 15in
- Weight: ~275lb (125kg)

## Standards and Compliance

- UL Certified
- FCC Part 15A
- Energy Star
- OCPP 1.6J
- CTEP
- TUV

## Other Features and Options

- RFID enabled
- Credit card reader available

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

