



## LW401-DC200

DC Fast Charger Dual Port  
200kW max

### KEY FEATURES

---

- » 32-inch touchscreen
- » Simultaneous charging
- » ISO 15118
- » Buy America compliant options available

# LW401-DC200

## Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 270A
- Output Voltage: 150-1000V DC
- Output Current: 350A (500A Boost)
- Output Power: 200kW
- Power Factor: >0.95
- Efficiency: >95% at full load
- 100kW per plug while simultaneously charging

## Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 19.7ft
- Cable management included

## Networking and Communications

- Wi-Fi & 4G LTE, Ethernet
- ISO 15118-2
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

## Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:  
-31°F to 131°F (-35°C to 55°C)
- Storage Temperature:  
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,561ft
- Impact Resistance: IK10

## Display and Indicators

- 32in FHD touch screen
- Resolution: 1920p X 1080p
- LEDs provide highly visible EVSE status indicators
- Customizable LED color

## Device Mounting

- Ground
- Device dimensions (WxHxD):  
27.5in X 80.7in (90.9in w/ LED Banner) X 27.5in
- Weight: 1102lb (500kg)  
With LED Banner: 1146lb (520kg)

## Standards and Compliance

- UL Certified
- Energy Star
- CSA
- FCC Part 15
- CTEP (NTEP)
- DIN70121
- NRTL (UL)
- OCPP 1.6J / 2.0.1

## Other Features and Options

- LED Banner (option)
- RFID enabled
- Buy America compliant options available
- Credit card reader available

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

