



LW401-DC600

Modular DC Fast Charger System
Up to 400kW

KEY FEATURES

- » 600kW Power Cabinet + 2x 400kW Dual Port Dispensers
- » Simultaneous charging at 150kW on 4 Ports (NEVI SPEC)
- » 32in touchscreen
- » ISO 15118
- » Buy America compliant options available

Electrical

- Input Voltage: 480V AC at 50/60Hz
- Cabinet Input Current: 722A AC
- Output Voltage: 200-1000V DC
- Output Current: 500A Boost
- Output Power: Up to 400kW
- Power Factor: ≥ 0.95
- Efficiency: $>95\%$ at full load
- Up to 400kW to 1 Plug, 300kW for 2 Plugs, and 150kW for 4 Plugs when simultaneously charging

Connector and Cable

- Dual CCS-1 (Liquid cooled)
- NACS options available
- High-quality flexible cable
- Cable length 16ft
- Cable management (included)

Networking and Communications

- Wi-Fi & 4G LTE
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:
-31°F to 131°F (-35°C to 55°C)
- Storage Temperature:
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,561ft above sea level
- Impact Resistance: IK10

Display and Indicators

- 32in FHD touch screen
- Resolution: 1920p X 1080p
- LEDs provide highly visible EVSE status indicators
- Customizable LED color

Device Mounting

- Ground
- Device dimensions (WxHxD):
Dispenser: 27.5in X 80.7in X 21.5in
Power Cabinet: 68.9in X 84.5in X 39.3in
- Dispenser Weight: 320kg
Power Cabinet Weight: 1200kg

Standards and Compliance

- UL Certified
- FCC Part 15
- CTEP (NTEP)
- DIN70121
- CSA
- NRTL (UL)
- OCPP 1.6J / 2.0.1

Other Features and Options

- LED Banner (option)
- RFID enabled
- Buy America Compliant options are available
- Credit card reader available

Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

